

DVT CB

VELCRO FATIGUE TESTER



VELCRO STRAP, UNDER LOAD OPEN - CLOSE
LIFE TEST DEVICE

DVT CB

TECHNICAL SPECIFICATIONS

- Opening and closing testing of strips which have certain width.

Performance of Velcro Strips can be tested in wet and dusty conditions.

■ USED IN

- Textiles
- Garments
- Bags
- Furniture.

■ APPROX. DIMENSIONS;

- Width: 610mm.
- Depth: 480mm.
- Height: 540mm.
- Gross weight : 91 Kg.

■ RELEVANT STANDARDS

- TS EN 1414 / 1415 / 12241
- TS 12829
- DIN 3415
- SATRA PM 123
- BS 7271

■ TECHNICAL INFORMATION

- Determine, opening and closing strength.
- Digital reading
- Construction, in compliance with the standards and easy to use.
- Velco Strips Test weights are supplied with tester.
- Can be used with every kind of Velcro strips.
- Rotation Meter provides, the pre determined number of tests.
- Selection of wet, dry, custom blended or dusty environment is provided
- Operation Voltage: 220V 50 Hz.

■ OPTIONAL ADDITIONS

- Depending on the different sized samples, provides appropriate fittings.
- Period values can be tried in any period of your chose

DEVOTRANS reserves the right to make changes to the brochure. Photographed models may not be the latest ones.