

DVT SKM 3

ROLLDOWN MACHINE



USED TO STICK BAND SAMPLES TO PREPARE
THEM FOR TEST

DVT SKM 3

TECHNICAL SPECIFICATIONS

Used to stick adhesive bands on plates making sure that there are no air bubbles.

USED IN

- Adhesive band manufacturing.
- Car industry (car manufacturers and their suppliers).

APPROXIMATE DIMENSIONS AND WEIGHT

- Width : 57 cm.
- Depth : 41 cm.
- Height: 24.5 cm.
- Weight: 26.8 kg.

RELEVANT STANDARDS

- TS EN 1943 / EN 1943
- TS EN 1939 / EN 1939
- ASTM D 3330
- ASTM D 903
- ASTM D 5170
- FINAT 2.1
- FINAT 06/2011
- JIS C2107

TECHNICAL INFORMATION

- Operating voltage: 220 Volt 50 Hz.
- Fuse: 6 Amperes.
- Cylinder period counter.
- Emergency stop button.
- Three cylinders to stick 3 bands simultaneously.
- Cylinder sticking direction: from left to right/from right to left.
- Cylinder speed setting button.
- Cylinder limit switch to adjust cylinder movement distance.
- #3 sticking plates.
- Rubber-coated cylinder.
- Stainless steel cylinder body.
- Cylinder body weight: 2 kg \pm 0,1 kg.

OPTIONAL FEATURES

- Selecting a different number of samples to be tested simultaneously.
- Uncoated cylinder (Stainless metal surface).
- Selecting a different cylinder weight.



**Hand-held
cylinder**

Note: Devotrans reserves the right to modify the equipment described in the brochure. The model in the picture may not be the latest one.

